

Technical Data SOLARIS

Material	stainless Steel		hot-dip galvanized steel				
Products	SOLARIS classic	SOLARIS live	SOLARIS classic	SOLARIS live	SOLARIS live extra	SOLARIS live plus	SOLARIS live intense
Solar module	monocrystalline silicon cells		monocrystalline silicon cells				
Output	55 / 58Wp		55Wp		110Wp		
Inclination	45°		adjustabel 45° / 60° / 75° / 90°				
Options	with frame / frameless		with frame				
Height of light	4.1m		3.4m / 4.1m		3.4m / 4.1m / 5.1m		4.1m / 5.1m
LED	12 (>60.000h)		12 (>60.000h)				2x12 (>60.000h)
Lumen	580lm		580lm		720lm		1.600-2.000lm
Colour temp.	Standard: 4.000k - Alternativ: 3.000K / 6.500K						
Motion sensor	-	incl.	-	incl.	incl.	incl.	incl.
Battery (inside pole)	NiMh						
Length of pole	4.8m		4.0m / 4.8m		4.0m / 4.8m / 5.8m		4.8m / 5.8m
all SOLARIS live:	Elektronics: individual, customizable, internet-adaptable lighting scenarios - dimming - adaptive brightness control condition monitoring - multiple series control etc.						

05.2020